

MBR30100CL

LOW VF SCHOTTKY RECTIFIER

VOLTAGE 100 Volts **CURRENT** 30 Amperes

FEATURES

- Ultra low forward voltage drop, low power losses
 - High efficiency operation
 - Lead free in comply with EU RoHS 2011/65/EU directives

MECHANICAL DATA


Case : TO-220AB, Plastic

Terminals : Solderable per MIL-STD-750, Method 2026

Weight : 0.065 ounces, 1.859 grams.

TO-220AB

Unit : inch(mm)



MAXIMUM RATINGS($T_A=25^\circ\text{C}$ unless otherwise noted)

PARAMETER	SYMBOL	VALUE	UNIT
Maximum repetitive peak reverse voltage	V _R RM	100	V
Maximum rms voltage	V _R M _S	70	V
Maximum dc blocking voltage	V _R	100	V
Maximum average forward rectified current per device per diode	I _{F(AV)}	30 15	A
Peak forward surge current : 8.3ms single half sine-wave superimposed on rated load	I _{FSM}	200	A
Typical thermal resistance per diode (Note 1)	R _{θJC}	2	°C/W
Operating junction temperature range	T _J	-55 to + 150	°C
Storage temperature range	T _{STG}	-55 to + 150	°C

Note : 1. Mounted on infinite heatsink.

MBR30100CL

ELECTRICAL CHARACTERISTICS($T_A=25^\circ\text{C}$ unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN.	TYP.	MAX.	UNIT
Breakdown voltage per diode	V_{BR}	$I_R=0.5\text{mA}$	100	-	-	V
Instantaneous forward voltage per diode	V_F	$I_F=3\text{A}$ $I_F=5\text{A}$ $I_F=15\text{A}$	$T_J=25^\circ\text{C}$	- - -	0.45 0.49 0.67	- - 0.72
		$I_F=3\text{A}$ $I_F=5\text{A}$	$T_J=125^\circ\text{C}$	- -	0.36 0.44	- -
	I_R	$V_R=70\text{V}$	$T_J=25^\circ\text{C}$	-	5	-
		$V_R=100\text{V}$	$T_J=25^\circ\text{C}$ $T_J=125^\circ\text{C}$	-	8.5	100 - μA mA




Fig.1 Forward Current Derating Curve




Fig.2 Typical Junction Capacitance




Fig.3 Typical Reverse Characteristics




Fig.4 Typical Forward Characteristics